



CELLFLEX® 1/4" superflexible cable

**FEATURES / BENEFITS**

• **Low Attenuation**

The low attenuation of CELLFLEX® coaxial cable results in highly efficient signal transfer in your RF system.

• **Complete Shielding**

The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.

• **Low VSWR**

Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.

• **Outstanding Intermodulation Performance**

CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.

• **High Power Rating**

Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.

• **Wide Range of Application**

Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.



1/4" CELLFLEX® Superflexible Foam Dielectric Coaxial Cable

**Technical features**

**APPLICATIONS**

<b>Applications</b>	OEM jumpers, BTS inter-cabinet connections, GPS lines, intended for outdoor usage
---------------------	---

**STRUCTURE**

<b>Size</b>		1/4
<b>Jacket Option</b>		Black
<b>Inner Conductor</b>	mm (in)	1.9 (0.075)
<b>Inner Conductor Material</b>		Copper-Clad Aluminum Wire
<b>Dielectric</b>	mm (in)	4.3 (0.17)
<b>Dielectric Material</b>		Foam Polyethylene
<b>Outer Conductor</b>	mm (in)	6.5 (0.26)
<b>Outer Conductor Material</b>		Corrugated Copper
<b>Jacket</b>	mm (in)	7.8 (0.31)
<b>Jacket Material</b>		Polyethylene, PE
<b>Cable Type</b>		Foam-Dielectric, Superflexible

**TESTING AND ENVIRONMENTAL**

<b>Fire Performance</b>		Halogene Free
<b>Installation Temperature</b>	°C(°F)	-40 to 60 (-40 to 140)
<b>Storage Temperature</b>	°C(°F)	-70 to 85 (-94 to 185)
<b>Operation Temperature</b>	°C(°F)	-50 to 85 (-58 to 185)



**ELECTRICAL SPECIFICATIONS**

Impedance, Ohm	Ω	50 +/- 1
Maximum Frequency	GHz	20.4
Velocity, percent	%	81
Capacitance	pF/m (pF/ft)	82 (25)
Inductance, uH/m (uH/ft)	μH/m (μH/ft)	0.207 (0.063)
Peak Power Rating	kW	5.5
RF Peak Voltage	Volts	740
Jacket Spark	Volt RMS	5000
Inner Conductor dc Resistance, Ω/km (Ω/kft)	Ω/1000 m (Ω/1000 ft)	10.5 (3.2)
Outer Conductor dc Resistance, ohm/1000 m (Ohm/1000 ft)	Ω/1000 m (Ω/1000 ft)	9 (2.75)
Return Loss (VSWR) Performance		Standard (for 40-2700, 3300-4200, 4400-5925 MHz) or Premium
Min. Return Loss (Max. VSWR)	dB (VSWR)	Standard 20 (1.222), Premium 24 (1.135)/ 23 (1.152)
Phase Stabilized		Phase stabilized and phase matched cables and assemblies are available upon request.
Temperature & Power		Standard

**MECHANICAL SPECIFICATIONS**

Cable Weight, Nominal	kg/m (lb/ft)	0.06 (0.04)
Minimum Bending Radius, Repeated Bends	mm (in)	25 (1)
Bending Moment, Nm (lb-ft)	Nm (lb*ft)	0.7 (0.5)
Tensile Strength	N (lb)	600 (135)
Recommended / Maximum Clamp Spacing	m (ft)	0.2 / 0.2 (0.67 / 0.67)



**ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)**

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
0.5	0.40	0.12	5.50
1	0.57	0.17	5.50
1.5	0.70	0.21	5.50
2	0.80	0.25	5.50
10	1.81	0.55	3.66
20	2.56	0.78	2.58
30	3.15	0.96	2.10
50	4.08	1.24	1.62
88	5.45	1.66	1.21
100	5.82	1.77	1.14
108	6.06	1.85	1.09
150	7.17	2.19	0.92
174	7.75	2.36	0.85
200	8.33	2.54	0.79
300	10.30	3.13	0.64
400	12	3.65	0.55
450	12.70	3.88	0.52
500	13.50	4.10	0.49
512	13.60	4.15	0.49
600	14.80	4.52	0.45
700	16.10	4.91	0.41
800	17.30	5.27	0.38
824	17.60	5.35	0.38
894	18.40	5.59	0.36
900	18.40	5.61	0.36
925	18.70	5.70	0.35
960	19.10	5.81	0.35
1000	19.50	5.94	0.34
1250	22	6.71	0.30
1500	24.30	7.41	0.27
1700	26.10	7.94	0.25
1800	26.90	8.20	0.25
2000	28.50	8.69	0.23
2100	29.30	8.93	0.23
2200	30.10	9.20	0.22
2400	31.60	9.60	0.21
3000	35.80	10.90	0.19
3500	39.10	11.90	0.17
4000	42.20	12.90	0.16
5000	48	14.60	0.14



**SCF14-50J**

1/4" CELLFLEX® Superflexible Foam-Dielectric Coaxial Cable

6000	53.40	16.30	0.12
7000	58.60	17.80	0.11
8000	63.40	19.30	0.10
9000	68.10	20.80	0.10
10000	72.60	22.10	0.09
12000	81	24.80	0.08
14000	89	27.20	0.07
16000	97	29.60	0.07
18000	105	31.90	0.06
20000	112	34.20	0.06
20400	113	34.60	0.06

External Document Links

Notes

Phase stabilized versions available upon request.  
Phase stabilized versions available upon request.